Series 6RO





Drinking fountains.

Perfect combination of elegance and practical design.

Made entirely from A-304 stainless steel, including the internal chassis.





Series 6RO

When the benefits of a durable drinking fountain with an elegant design are required.

Elegant circular top plate structure with an attractive design. Hygienic water jet outlet protection. Easily regulated cold water temperature (thermostat). There is also the possibility to drink with cups for the models with cup fillers (LV models).

Models

M-6ARO

- Cold water jet, push button.

M-6AROLV

- Cold water jet, push button.
- Cup filler

M-2ARO

- No cooling system.
- Room temp. water jet, push button

Installation by means of three basic connection points.

The installation of a purification filter is highly recommended for better water quality.

Accessories

There is a specific catalogue for filters.



PURIFICATION FILTERS:

It is recommended to install an activated carbon purifying filter to obtain water in optimal condition. Consult options.

Technical data

Series 6RO

Cooling Power (W)	350
Power consumption (W)	200
Voltage 230V 50Hz single-phase (A) (Consult other options)	0.9
Cooling capacity (Room temp.: 30°C, Input temp.: 27°C, Output temp.: 17°C) (I/h)	30
Water output speed (I/h)	60
Cold water output temperature (Regulated by thermostat) (°C)	4-11
Water tank capacity (I) (Optional: Stainless steel cooling system. Direct chill)	4.5
Refrigerant gas (CFC-free)	R-134a
Net weight (kg)	28





HEADQUARTERS AND FACTORY

Ronda de Llevant, 10 08820 El Prat de Llobregat Barcelona (Spain) T. +34 934 358 546 F. +34 934 350 604

INTERNET

www.canaletas.es www.canaletas.com infox@canaletas.es

