

# Drinking fountain with reverse osmosis

With integrated reverse osmosis filtration designed for the hardest water.

Superior quality, made entirely from stainless steel.



Model: M-66ALV RO






## Series 601

With integrated reverse osmosis filtration for the hardest water. Designed to fill up small bottles or drink directly.

The water cooler includes a high capacity filtration system that eliminates suspended solids and microorganisms to ensure a high quality of pure water. The use of this filtration system is recommended in areas where the municipal water supply is of inferior quality and requires a higher capacity filter. A fountain of superior dimensions that gives it a great presence and robustness.



#### Model

#### M-66ALV RO

Pedal: cold water

Push button: room temperature

Pedal + button: mixted

Bottle-filler (small bottles) operated by button for cold water

### **Accessories**

#### FILTERS - TANK

Reverse osmosis system composed by 3 filters and a reverse osmosis membrane, that requires periodic changes. Tank for the osmotized water.

#### INTEGRATED OSMOSIS SYSTEM

Compact design that ensures reliable water flow between the various stages of filtration, avoiding the need for multiple connections or loss of water.

- 4 Stages of filtration with a pump: Guarantees a high quality of water.
- Very easy to mantain: With no possibility of error for the user.
- High performance and high efficiency: High water production 250 liters a day. High rate of input water use: 35%.
- Protection: Prevents sensitive components, such as the pump, from operating without water.
- Great comfort: Greater silence when activating the water dispensing buttons.

#### Technical data

Cooling power (W)	400
Power consumption (W)	200
Voltage 230 V 50Hz single-phase(A) (Consult other options)	0,9
Cooling capacity (Room T.: 30°C, Input T.: 27°C, Output T.: 17°C) (I/h)	35
Cold water output temperature (Regulated by thermostat) (°C)	4-11
Refrigerant gas (With no CFC)	R290
Dimensions (mm). Hight x Width x Depth. Models with LV + 210 mm	1030 x 360 x 470

#### **HEADQUARTERS AND FACTORY**

Ronda de Llevant, 10 08820 El Prat de Llobregat Barcelona (Spain) T. +34 934 358 546 F. +34 934 350 604

www.canaletas.es www.canaletas.com infox@canaletas.es

